

Ran

Additional information please contact:

Borr Drilling Limited
E. Pearman Building, 2nd Floor
9 Par-la-Ville Road,
Hamilton HM11, Bermuda

marketing@borrdrilling.com - www.borrdrilling.com

High Specification Jackup

General Description

Design / GenerationKFELS Super A
Constructing Shipyard Keppel KFELS Singapore
Year Entered Service / Significant Upgrades..... 2013
Classification ABS, A1 Self-Elevating Drilling Unit
Flag Liberia
Overall Dimensions 246ft (L) x 232ft (W) x 31ft (D)
Legs 3 x 525ft
Drafts 22ft
Accommodation 120 Persons
Displacement 51852 kips
Variable Deck 8208 kips operating/ 6508 kips storm operating/ 5905 kips transit
Transit Speed up to 4 knots
Operating Water Depth 400ft
Maximum Drilling Depth 35,000ft

Drilling Equipment

Derrick NOV SSBN. 170ft high with 40ft x 40ft base
Hookload Capacity 2,000,000lbs
Cantilever 75 ft/ 15 ft Port & 15ft Stbd
Drawworks NOV ADS-10Q, max hookload 1145 st with 16 lines. (4) 1500 hp motors suitable for 2" Drill Line
Rotary Table NOV 495, 49-1/2" opening, hydraulic drive. Rated to 1000 st.
Top Drive NOV TDS-1000. 907 mt load rating, 1150 hp motor. Max RPM 270, max torque 65,500 ft/lbs. Max MU torque 95,000 ft/lbs, Max BO torque 110,000 ft/lbs. (2) IBOP 3 1/16" - 15k Psi
Tubular Handling NOV ST-160, 3 1/2" to 10" OD drill pipe & drill collars. Make up torque 140,000 ft/lbs, breakout torque 160,000 ft/lbs. Spinning speed 80 rpm (5" OD). Spinning torque 3467 ft/lbs
Mud Pump (3) NOV 14-P-220 triplex pump, each driven by 1,150hp motor (NOV Baylor DM27) 7,500psi rated
Solids Control (5) NOV VSM-300 shale shakers

Power & Machinery

Main Power (6) Caterpillar 3516C-HD diesel engines rated at 2,150hp at 1200rpm each with Kato generator rated to 1,500 kW
Emergency Power (1) Caterpillar 3508B, rated at 1237 hp at 1800 rpm with Stamford HCM634K2 generator rated at 910 kW

Storage Capacities

Fuel Oil 4,681 bbls
Liquid Mud 5,585 bbls
Base Oil 1,476 bbls
Brine 1,728 bbls
Drill Water 19667 bbls
Potable Water 3,543 bbls
Bulk Material (mud + cement) 17,600 cu ft
Sack Storage 5,000 sacks

BOP & Well Control Equipment

BOP Rams (2) Cameron double ram 18-3/4" 15K psi
BOP Annular (1) Cameron 18-3/4" 10K psi DL Annular
BOP Handling (2) J.D. Neuhaus EHZ 100 hoists rated to 100 mt each
Diverter Cameron 47", 1,000 psi with 16 in flow lines

Mooring Equipment

Mooring Winches (4) Cargotec electric winches rated at 41 mt. Holding brake rated to 144 mt.
Wires 2,000ft x 2" galvanized wire rope

Cranes

Deck Cranes (3) Seatrax cranes rated to 63mt each. (2) cranes with 120ft booms & (1) crane with 150 ft boom
Pipe Handling (1) Outreach PKM700T knuckle boom crane with 82ft boom, rated to 2.3mt with 82ft boom without pipe grab attached, located starboard side of the cantilever

Special Features & Other Information

Helideck Rated for: S-92 and S-61N. Cap 437
Work Offline (WO) NOV SBBC 22,000lb (SWL) / NOV PRS-8-I 22,000lb (SWL)



These specifications are intended for general reference purposes only, as actual equipment and specifications may vary based upon subsequent changes, the contract situation and customer needs. All equipment shall be operated and maintained at all times, in compliance with Borr Drilling standard operating manuals, policies and procedures, and within its stated operational limits or continuous rated capacity, in order to assure maximum operational efficiency.

