

Titania

Additional information please contact:

Borr Drilling Limited
E. Pearman Building, 2nd Floor
9 Par-la-Ville Road,
Hamilton HM11, Bermuda

marketing@borrdrilling.com - www.borrdrilling.com

High Specification Jackup

General Description

Design / Generation Friede & Goldman JU2000E
Constructing Shipyard..... Dalian Shipyard, China
Year Entered Service / Significant Upgrades 2014
Classification ABS, A1, Self-Elevating Drilling Unit
Flag Singapore
Overall Dimensions 231ft. Long x 249ft. Wide x 31 ft deep
Legs.....(3) 548 ft. long, Triangular
Drafts 22 ft at load line
Accommodation 140 persons
Displacement 50,693 kips
Variable Deck..... 14,500 kips drilling / 6,602 kips transit
Operating Water Depth.....400 ft. designed / 400 ft. outfitted
Maximum Drilling Depth..... 35,000ft

Drilling Equipment

Derrick TTS type DD-1000 III; 210 ft high with 40 ft x 40 ft base
Hookload Capacity 2,100,000 lbs gross nominal capacity
Cantilever 75 ft x 15ft x 15ft
Drawworks Cameron TTS Ultra hoist SG 1060-6000 Max hook load 1,855 kips with 14 lines. suitable for 2" drill line
Rotary Table TTS-HYD powered 49.5" table opening, hydraulic drive
Top Drive Cameron TTS STD-1000-AC, 2,000 kips load rating, max continuous torque 98,000 ft/lbs
Tubular Handling TTS-JIM 10T LR Iron Roughneck.
Mud Pumps (3) Aker Wirth TPK 2200 triplex pumps 2,200hp
Solids Control (4) MI Swaco MD-3 shale shakers

Power & Machinery

Main Power (6) Caterpillar 3516C-HD diesel engines rated at 2,150hp each with Caterpillar SR4B generator rated to 1,534kW
Emergency Power (1) Caterpillar C32 diesel engine rated at 1,333hp.
..... (1) Caterpillar Generator, 900kW

Storage Capacities

Fuel Oil 4,075 bbls
Liquid Mud 5,257 bbls
Base Oil 1,340 bbls
Brine 1,340 bbls
Drill Water 8,290 bbls
Potable Water 3,522 bbls
Bulk Material (mud + cement) 19,776 cu-ft
Sack Storage..... 5,000 sacks

BOP & Well Control Equipment

BOP Rams (2) Cameron TL double ram 18-3/4" 15k psi BOP
BOP Annular (1) Cameron DL annular 18-3/4" 10k psi BOP
BOP Handling (2) TTS hoists, rated 125mt
Diverter Vetco Gray / KFDJ, 49.5" spherical diverter rated to 500psi

Mooring Equipment

Mooring Winches 4 x Pellegrini AT40000/E, 120hp 40 mt Pull
Anchor Lines 4 x 3,000 ft, 2 in Diameter IWRC
Anchors 4 x Flipper Delta 7.5mt

Cranes

Cranes (3) Liebherr CBO 3600-75 cranes, 75mt capacity, 120ft boom

Special Features & Other Information

CTU TSC 8 x lift points total tension 600kips
Helideck S61N & S92
Pipe Handling Crane (1) TTS type PDC GPOKTop 680-12-25, 10mt SWL



These specifications are intended for general reference purposes only, as actual equipment and specifications may vary based upon subsequent changes, the contract situation and customer needs. All equipment shall be operated and maintained at all times, in compliance with Borr Drilling standard operating manuals, policies and procedures, and within its stated operational limits or continuous rated capacity, in order to assure maximum operational efficiency.

